## 2018 Subaru Crosstrek®

## Specifications

Vehicle type	5-door, 5-passenger sport utility vehicle		
Engine	4-cyl. horizontally opposed (Boxer), aluminum cylinder head		
9	and block		
Displacement	1,995 cc / 122 cu. in.		
Bore x Stroke	3.31 in. x 3.54 in.		
Compression ratio	12.5:1		
Horsepower	152 @ 6,000 rpm		
Torque	145 lbft. @ 4,000 rpm		
Fuel system	Direct fuel injection, electronic throttle control		
Valvetrain	Double overhead chain-driven camshafts (DOHC), 4 valves per		
	cylinder, Dual Active Valve Control System (DAVCS) controls		
	valve timing on intake camshafts, tumble generator valves		
Ignition	Direct		
Transmission			
Standard	6-speed manual with Incline Start Assist		
Optional	Lineartronic® CVT (continuously variable transmission).		
	(Standard for Limited.) Includes X-MODE and Hill Descent Control; base model features Low Shift Mode; Premium and Limited feature driver-selectable 7-speed manual shift mode		
	and steering wheel paddle		
Transmission ratios	6-speed manual	CVT shift ratios (for manual	
	·	control mode)	
1	3.818	3.600	
2	1.947	2.155	
3	1.296	1.516	
4	1.029	1.092	
5	0.825	0.843	
6	0.738	0.667	
7		0.557	
Rev.	4.072	3.687	
Final drive	4.444	3.900	
Symmetrical All-Wheel Drive	Standard on all models		
M/T AWD system	Continuous All-Wheel Drive with viscous-coupling locking center differential		
CVT AWD system	Active Torque Split All-Wheel Drive with electronically managed continuously variable hydraulic transfer clutch		
Stability/traction control		with all-wheel, all-speed traction	
Stability, addition dominor	control (TCS) and rollover sensor		
Chassis			
	safety structure		
Suspension	4-wheel independent, raised with Stablex dampers		
Front	MacPherson-type struts, lower L-arms, coil springs, stabilizer		
	bar		
	Hydraulic engine mounts on CVT models		
Rear	Double wishbone, coil springs, stabilizer bar		
Brakes	Power-assisted 4-wheel disc with Electronic Brake-force Distribution (EBD) and 4-channel / 4-sensor ABS with Brake		
	Assist and Brake Override safety systems Active Torque Vectoring		

	11.6-in. ventilated front discs and 10.8-in. solid rear discs		
Steering Rack-and-pinion with electric power assist			
_	Ratio: 13:1 Turns, lock-to-lock: 2.6		
	Turning circle: 35.4 ft.	ng circle: 35.4 ft.	
Wheels	17 x 7-in aluminum alloy Limited: 18 x 7-in aluminum alloy		
Tires	225/60R17 98H all-season		
	Limited: 225/55R18 98H all-season		
Exterior Dimensions			
Wheelbase	104.9 in.		
Length	175.8 in.		
Width	71.0 in. (79.0 in. including mirrors)		
Height	63.6 in. with roof rails		
Min. road clearance	8.7 in.		
Angle of approach	18.0 deg.		
Angle of departure	29.0 deg.		
Ramp breakover angle	19.7 deg.		
Track (front/rear)	61.0/61.2 in.		
Curb weight (lb.)	2.0i 6-speed manual: 3,113		
	2.0i CVT: 3,157 2.0i Premium 6-sp.: 3,142		
	2.0i Premium CVT: 3,186 Limited CVT: 3,230		
Interior Dimensions			
Headroom (f/r)	39.8/38.0 in. with moonroof: 37.6 /37.8 in.		
Legroom (f/r)	43.1/36.5 in.		
Hip room (f/r)	55.1/55.2 in.		
Shoulder room (f/r)	56.7/55.6 in.		
EPA interior volume	100.9 cu. ft. with moonroof: 97.5 cu. ft.		
Trunk lift over height	30.9 in.		
Cargo volume	Rear seats up/down: 20.8 cu. ft./55.3 cu. ft.		
Max. load floor length	Rear seats up/down: 32.3/64.2 in.		
Fuel economy	6-speed manual	CVT	
EPA-estimated	23/29/25	27/33/29	
city/highway/combined			
mpg			
Fuel tank capacity	16.6 gal.		