2021 Subaru Crosstrek

Specifications

Vehicle type	5-door, 5-passenger sport-utility vehicle			
Engine	Base and Premium	Sport a	and Limited	
Displacement	1,995 cc / 122 cu. ir	n. 2,4980	c / 152.0 cu. in.	
Bore x Stroke	3.31 in. x 3.54 in.	3.70 in	. x 3.54 in.	
	(84.0mm x 90.0 mm) (94.0mm x 90.0mm)			
Compression ratio	12.5:1	12.0:1		
Horsepower	152 @ 6,000 rpm		5,800 rpm	
Torque	145 lbft. @ 4,000 rpm			
Fuel system	Direct fuel injection, electronic throttle control			
Fuel requirement	Regular / 87 AKI			
Valvetrain	Double overhead chain-driven camshafts (DOHC), 4 valves per cylinder, Dual Active Valve Control System (DAVCS) controls valve timing on intake camshafts; tumble generator valves			
Ignition	Direct			
Powertrain management	Models equipped with Lineartronic® CVT (continuously variable transmission) include Auto Stop-Start system fuel-saving technology and Subaru SI-DRIVE driver-selectable powertrain management system with Intelligent and Sport modes and steering wheel control switches.			
Transmission				
Standard for Base and Premium	6-speed manual with Incline Start Assist			
Standard for Sport and Limited; optional for Base and Premium	 Lineartronic® CVT (continuously variable transmission) with Incline Start Assist Premium, Sport and Limited feature driver-selectable 8-speed manual shift mode and steering wheel paddle shift control switches Base trim has Low Shift Mode Premium and Limited have X-MODE and Hill Descent Control Sport has Dual-mode X-Mode with SNOW/DIRT and DEEP SNOW/MODE selectable settings 			
Transmission ratios	6-speed manual	2.0-liter engine CVT ratios (manual control mode)	2.5-liter engine CVT ratios (manual control mode)	
1	3.818	4.066	4.066	
2	1.947	2.600	2.628	
3	1.296	1.827	1.911	
4	1.029	1.377	1.490	
5	0.825	1.061	1.166	
6	0.738	0.836	0.914	
7		0.668	0.717	
8		0.559	0.559	
R	4.073	4.379	4.379	
Final drive	4.444	3.900	3.700	
Symmetrical All-Wheel Drive	Standard on all models			
M/T AWD system	Continuous All-Wheel Drive with viscous-coupling locking center differential			

OVE AVAID avertons	Astina Tanana Calit	All M/h a al Duiva voith alaat	and a plice a particular of	
CVT AWD system	CVT AWD system Active Torque Split All-Wheel Drive with electronically controlled variable hydraulic transfer clutch			
Stability/traction control	Vehicle Dynamics Control with all-wheel, all-speed traction control (TCS) and rollover sensor			
Chassis	Unitized body construction, Ring-shaped Reinforcement Frame safety structure			
Suspension	4-wheel independent, raised with Stablex dampers			
Front	MacPherson-type struts, lower L-arms, coil springs, stabilizer bar			
	Hydraulic engine mounts on CVT models			
Rear	Double wishbone, coil springs, stabilizer bar			
Brakes	Power-assisted 4-wheel disc with Electronic Brake-force Distribution			
		BD) and 4-channel / 4-sensor ABS with Brake Assist and Brake		
	Override safety systems and Active Torque Vectoring			
	11.6-in. ventilated front discs and 10.8-in. solid rear discs			
Steering	Rack-and-pinion with electric power assist			
	Ratio: 13:1			
	Turns, lock-to-lock: 2.6			
	Turning circle: 35.4 ft.			
Wheels	Base, Premium and Sport: 17 x 7-in aluminum alloy			
	Limited: 18 x 7-in aluminum alloy			
Tires	Base, Premium and Sport: 225/60R17 98H all-season			
	Limited: 225/55R18 98H all-season			
Exterior Dimensions				
Wheelbase	104.9 in.			
Length	176.5 in.			
Width	irrors: 79.0 in. on Prem; 7	9.5 in. on Sport and		
11.50	Limited			
Height	63.6 in. with roof rails			
Min. road clearance	8.7 in.			
Angle of approach	18.0 deg.			
Angle of departure	28.6 deg.			
Ramp breakover angle	19.7 deg.			
Track (front/rear)	61.0/61.2 in.			
Curb weight (lb.)	Base w/ 6-speed manual: 3,117			
3 ()	Base w/CVT: 3,188			
	Premium w/6-speed manual: 3,146			
	Premium w/ CVT: 3,223			
	Sport (CVT only): 3,265			
	Limited (CVT only): 3,298			
Interior Dimensions				
Headroom (f/r)	39.8/38.0 in. with moonroof: 37.6 /37.8 in.			
Legroom (f/r)	43.1/36.5 in.			
Hip room (f/r)	55.1/55.2 in.			
Shoulder room (f/r)	56.7/55.6 in.			
EPA interior volume	100.9 cu. ft. with moonroof: 97.5 cu. ft.			
Cargo liftover height	30.9 in.			
Cargo volume	Rear seats up/down: 20.8 cu. ft./55.3 cu. ft.			
Max. load floor length	Rear seats up/down: 32.3/64.2 in.			
Fuel economy	6-speed manual	2.0-liter with CVT	2.5-liter with CVT	
EPA-estimated	22/29/25	28/33/30	27/34/29	
city/highway/combined			, .	
mpg				
Fuel tank capacity	16.6 gal. (all)	ı		